

STRONG ENERJİ SAN.VE TİC.LTD.ŞTİ.

When you purchase the %6,6 INFINIUM P5500+ %0,06 INFINEUM C9417 additive mentioned below and use it in its production; Contains allof the following 5W40 SN PLUS approvals when using the recommended formulation.

INFINEUM P5500

- **Optimized treat rates for API performance**
- **Multiple viscosity grades in PCMO :**
 - ✓ 0W-16, 0W-20, 0W-30
 - ✓ 5W-20, 5W-30, 5W-40
 - ✓ 10W-30, 10W-40
 - ✓ 20W-40, 20W-50
- **Formulations** with Infineum SV261 and Exxon group II and Etro group III base oils available upon request
- Boosted with Infineum C9417, Infineum P5500 can be used for **MCO applications** (JASO MA2 claim and MB claim with Infineum S1889 booster) in 10W-30, 10W-40 and 20W-40 grades

	PCMO Infineum P5500	MCO Infineum P5500 + Infineum C9417
API SP	7.0%	Not available
API SN/SN Plus	6.6%	6.6% + 0.06%
API SM	6.2%	6.2% + 0.12%
API SL (1)	5.3% + Infineum C9417 (0.25%)	
API SJ	5.3%	5.3% + 0.25%
API SG	4.8%	4.8% + 0.35%

(1) API SL, JASO T 903:2016 have P limit of 800ppm min



BRENNTAG KİMYA TİC. LTD. ŞTİ
 Kavacık 11/1 Etiler Cad. Muhtar Sk. No
 K:1 T:1 Kat:1 Beşiktaş - İSTANBUL
 Tel: (0212) 331 25 36
 Faks: (0212) 331 187 048 6012
 Tic. Sic. No: 268870

